

## Playground safety tile – 300 cm (FS)


This 10 cm thick playground safety tile provides certified impact protection up to a critical fall height of 300 cm (BS EN 1177) and is suitable for playgrounds indoors and outdoors. It is installed beneath play and climbing equipment such as climbing walls, bouldering areas, net and rope play equipment, tall swing frames and climbing towers, creating a durable and safe play surface.

The tiles are laid in a half-bond pattern and stabilised with lateral plastic interlocking connectors; a continuous perimeter edging is required. The strongly profiled underside ensures reliable drainage so that the surface can be used safely even in wet conditions. Frost-resistant, UV-stabilised, water-permeable and toxicologically safe, the tile is a low-maintenance, long-term safety surface for both public and private play areas.

### Product data

Colour	<b>Rose</b>	Weight	<b>11.17 kg/Piece = 44.68 kg/m<sup>2</sup></b>
Installation	<b>Connecting pins - plastic plugs</b>	Conversion	<b>1 m<sup>2</sup> = 4 Piece</b>
Packaging	<b>500 x 500 x 100 mm</b>	Useful size	<b>500 x 500 x 100 mm</b>

## Properties




### Colour Rose

Inspired by the red rose, Rose is a warm, vibrant shade of red that exudes an invigorating and powerful presence. Rose is dynamic and appealing, creating a sporty and motivational atmosphere in its surroundings. The red rubber granules are made from newly manufactured, UV-resistant and non-toxic EPDM, ensuring exceptional colour stability. The Rose colour is particularly suitable for environments where a warm and energetic design is desired.



### Material

The product has a two-layer structure, but is manufactured in a single pressing process, making it monolithic. The bottom layer, known as the functional layer, is made of black rubber granulate derived from the recycling of end-of-life tyres (ELT). Chemically, this granulate consists of a mixture of natural rubber (NR) and styrene-butadiene rubber (SBR). The top layer, known as the tread, is made from newly manufactured, fully coloured and toxin-free EPDM (ethylene-propylene-diene rubber) granules. This product meets the highest standards of safety, durability and functionality.



### Installation

On two sides - between each row of tiles - the tiles are connected by means of lateral connecting pins (plastic plugs). The tiles must be laid in a half-bond pattern, i.e. each row of tiles is offset by half a tile (T-joint). In this pattern, each tile is connected to two tiles in the row above and two tiles in the row below using plastic plugs. These plugs prevent lateral movement of the tiles, but do not restrict movement along the longitudinal axis of the plugs. For this reason, a perimeter edging must be installed around the tiled surface.



### Structure of the underside

The underside of the tile features an embossed pattern of inverted truncated pyramids. These truncated pyramids, approximately 75 mm high, are specifically designed to enhance the tile's weather resistance, dimensional stability and shock-absorbing properties, while ensuring efficient water drainage in outdoor applications. The tiles can be installed on solid surfaces such as concrete, asphalt, interlocking paving or flagstones, as well as on roof waterproofing systems or plastic grass meshes. Please refer to the installation guidelines for correct application.

## Playground safety tile – 300 cm (FS)

### Characteristics



#### Colourfast and UV-resistant

The surface made of EPDM rubber granules is colourfast and long-term UV-resistant (sun).



#### Indoor & Outdoor

Weather and frost resistant – suitable for versatile indoor and outdoor use.



#### Frost resistant

Resistant to frost and freezing water within the material – no cracking, tearing or breaking.



#### 300 cm critical fall height (EN 1177:2018)

TÜV-certified playground surface. Safety for private and public areas. Critical fall height: 300 cm.



#### Suitable for chlorinated water

Good resistance to chlorinated water, chlorinated cleaning agents and swimming pool water.



#### Toxicologically safe

No impermissible pollutant emissions, initial rubber odour dissipates over time.



#### Cfl-s1

Fire behaviour according to EN 13501-1: Cfl-s1  
Limited contribution to fire – Low smoke emission

### Comparative values

The comparison of technical data on a scale from 1 to 5 provides a practical way of objectively comparing the relevant properties of WARCO products, making it easier to find the most suitable product for the intended application. Detailed information on the scale values and their calculation can be found online on the product detail page.



Water Permeability (EN 12616) – Rating 4 = Infiltration approx. 600 mm/h (600 l/h/m<sup>2</sup>)



Slip resistance class DS (EN 14041) - Scale value 5 = Coefficient of friction approx. 0.6



Shock, vibration, and impact sound insulation – Scale value 5 = excellent damping



Thermal insulation – Scale value 5 = Thermal conductivity approx. 0.07 W/(m·K)



Apparent density - scale value 2 = 780 to 840 kg/m<sup>3</sup>



Slip resistance (EN 16165) – Scale value 4 = mean acceptance angle approx. 16°, group R10



Compressive strength - Scale value 2 = approx. 0.75 mm residual dent after 24 hours of unloading (BS 7188)



Abrasion resistance – Resistance to abrasive wear – Scale value 2 = "good" (BS 7188)

**Michael Schladt**  
**WARCO Gulvbelægninger**  
Andergasse 17  
67434 Neustadt an der  
Weinstraße

WARCO Gallery  
Klemmhof 9  
67433 Neustadt an der Weinstraße  
Onsdag til fredag, 10:00 - 16:00

**Faglig rådgivning**  
**+49 6321 9152391**

E-mail: [info@warco24.dk](mailto:info@warco24.dk)  
Internet: [www.warco24.dk](http://www.warco24.dk)